



SUBAL

Media Release

SUBAL ND4 for Nikon D4

With the SUBAL ND4 for the Nikon D4, SUBAL offers an aluminium housing for the latest development of full-frame-SLR cameras from Nikon with no reduction in the angle of coverage! There is no limit in creativity for the underwater photographer!

The SUBAL ND4 allows access to all functions of the Nikon D4 including Live view and Info.

Ergonomic placement of all important controls provides convenient and comfortable handling of the camera functions. Special attention was made to the position of the front and rear main dial and the lever for the display illumination.

The camera is mounted on a saddle for precise positioning inside the housing so that wrong positioning is impossible. A 4 mm main-O-ring and the SUBAL QuickLock system make it virtually impossible to close the lid if the O-ring is not lying correctly in its groove. Maximum security is assured.

Generous shading of the LCD-monitor provides a glare-free view to the brilliant image of the camera monitor which is ideal when using the HD-video function of this camera.

Threaded holes in the base of the housing allow the mounting of trays etc.

On the top of the housing there is a mounting plate with a threaded hole for mounting a light-weight aiming light.

The housing incorporates an excellent viewfinder optic for full frame viewing.

Optionally the housing can be assembled with the magnifying Viewfinder Optic **GS 180** as well as with the also magnifying, 360° revolvable, Viewfinder Optic **WS45**.

The new Prism finder **PS-30** shows the viewfinder image full sized with a viewing angle of 30°. The PS-30 has a long eye relief which is especially helpful for video shooting.

The viewfinder systems are interchangeable and can be mounted easily by the user.

As with all our products choice of materials, machining, surface protection and finish conform with SUBAL's well known standards of reliability and workmanship.

All SUBAL ports with bayonet mount can be used with this housing.

Controls/Functions:

Power On - Off / Display Illumination, Shutter Release, Zoom (manual focus), Front and Rear Main Dial, Lens Release, Focus Mode Selector (M-S-C), Metering mode control, Movie Record Button, Mode Selector, AF - Lock, AF - ON, Port Lock.

Push Buttons for:

Mode, Exposure Compensation, Bracketing, Flash Sync Mode, Lock,), Metering mode control, Rec. Start/Stop, Playback, Delete, Menu, Thumbnail, Protect, OK, ISO, Quality, White Balance, Microphone, Multi Selector, Info, Live View, AF-On, FN, AF-Mode.

Technical Data

Seawater resistant aluminum alloy, machined from solid, extreme surface hardening and corrosion resistance through HardCoating. 3-layer powder coating. All parts manufactured from anodized and hard coated acid proof stainless steel or high quality plastics. Seals are seamless precision O-rings. SUBAL QuickLock latching system.

Configuration:

- W x H x D Approx. 280 x 215x 160 mm (w/o port and handles)
- Weight Approx. 3,5 kg (w/o port and accessories)
- Buoyancy All but neutral (depended on used port and accessories)
- 2 Flash connectors Optionally Nikonos V, IKELITE or Subtronic S6 sockets.
- Strobe arm mounts Two 25 mm T-plates, TLC- or Ultralight base optional
- Max. Depth rating 70 m (210 ft) optionally 120m (360 ft)

For inquiries/further information please call:

SUBAL Europe, R. Sempert

Post Box 1607

D-84484 Burghausen

Tel: +49 8677 65897, Fax: +49 8677 65982. e-mail: europa@subal.com

Pictures enclosed