

# SUBAL CP5

for Nikon Coolpix 5000



## Controls/Functions:

All push buttons, command dial, camera/recorder mode selector, AF lock, control window for camera display and AF/ready light.

Finder/monitor: 45° view of the extended monitor, straight view (for vertical frame picture composition) when monitor is folded back.

## Technical data:

Seawater resistant aluminium alloy, machined from block, extreme surface hardening and corrosion resistance through HardCoating. All parts manufactured from anodized and hard coated aluminium, acid proof stainless steel or high quality plastics. Seals are seamless precision O-rings.

SUBAL Quicklock system left, hook-in hinge right.

Handle left, integrated hand strap right, optical leak alert.



The **SUBAL CP5** represents a logical progression toward a digital future in underwater photography. Designed with much attention to detail and without compromise when it comes to functionality the housing allows access to most functions of this amazing five megapixel camera. The specially designed mounting slide prevents any errors and makes precise camera installation a breeze. A generously dimensioned O-ring and SUBAL's unique Quicklock system, which makes it impossible to close the lid if the O-ring is not in its groove, provide maximum security. To facilitate framing and picture composition two separate finder windows afford either straight view with unfolded monitor or 45° with folded monitor. This new and exclusive feature facilitates close-up photography near the ocean floor as well as picture composition when taking upright frames. The CP 5 comes complete with a high quality, anti-reflex coated mineral glass flat port. An optional dome port allows use of the wide-angle converter WC-E68 as well as the fisheye converter FC-E6. As with all our products choice of materials, machining, surface protection and finish conform with SUBAL's well known standards of reliability and workmanship.



## Configuration:

- **Width x height x depth** 205 x 130 x 100 mm
- **Weight on land** Ca. 1,6 kg (without port)
- **Weight in water** Nearly neutral
- **Flash connector** 1 Nikonos V socket, second socket optional
- **Strobe arm attachment** 1 T-plate 25mm, TLC or Ultralight shoe optional;
- **Maximum depth rating** 70 m

