

SUBAL D10

for NIKON D100



SUBAL's first housing for digital SLR cameras consequently follows the very successful and supremely approved design strategy of the new generation of underwater housings. The ergonomic placement of all the important controls provides comfortable handling of the camera's functions without moving your hand from the handle. The camera is mounted on a saddle which provides precise positioning inside the housing, mounting failures are nearly impossible. A large O-ring and the new SUBAL Quick Lock latching system, which makes it impossible to close the lid if the O-ring is not in its groove, provides maximum security. Threaded holes on the base and in the top-accessory shoe allow mounting of trays or aiming lights etc. The housing incorporates an excellent viewfinder optic for full frame viewing.

Controls :

Shutter Release, Power Switch, Front and Rear Main Dial, Manual Focus/Zoom, Flash Sync Mode, Exposure Compensation, Display Light, Function Dial, Lens Release, M-S-C, Mode dial, M-S-C, Metering Selector, AF-Lock, Multi Selector, BKT, Flash Exposure Compensation, Monitor, Menu, Thumbnail View, Protect, Enter, Delete.

Technical data :

Seawater resistant aluminium alloy, machined from block, extreme surface hardening and corrosion resistance through HardCoating. All parts manufactured from anodized and hard coated aluminium, acid proof stainless steel or high quality plastics. Seals are seamless precision O-rings. O-Rings in hard coated glands. SUBAL QuickLock closing system.

W x H x D:

Approx. 240 x 182 x 140 mm (w/o Port and handles)

Weight:

Approx. 2,4 kg (w/o Port and accessories)

Buoyancy:

Nearly neutral (depended on used Port and accessories)

Flash connector:

2 Nikonos V TTL sockets (Standard). Other systems available

Flash arm mounts:

2 x 25mm T-plates, TLC- or Ultralight base optional

Max. Depth rating:

70 Meter (210 ft)

