



SUBAL N99 SUBAL N99/DL

for NIKON F90/F90X

The SUBAL N99 is available with two different viewfinder systems for you to choose.

Standard Version:

The housing's viewfinder port is located as close to the camera's viewfinder as possible. The High-Eyepoint viewfinder on Nikon F801 and F90 can be viewed at maximum magnification virtually full frame, especially with a low volume mask.

DeLuxe Version:

Specifically designed for the High-Eyepoint viewfinder, the DeLuxe viewfinder gives full and comfortable viewing of the whole frame including the information panel with a minimum reduction of the viewfinder image. It also incorporates a +/- 3 dioptre adjustment for spectacle wearers. The viewfinder housing creates more space for your regulator and makes handling more comfortable.

Controls:

Camera Power, Shutter release, Zooming, Aperture, Control Dial, Focus (manual), Focus Mode Select, Meter Mode Select, Exposure Compensation, AF Lock, LCD-Panel/Viewfinder Illumination

Technical data:

Marine grade aluminum alloy, fully hard anodized. All parts are made of anodized light metal, stainless steel or high quality synthetics. Seamless precision O-Rings. SUBAL QuickLock closing.

The **SUBAL MINIFLEX-N** is the smallest and lightest underwater housing yet it offers the most comprehensive features. Only slightly larger than your Nikon N90 camera, the housing fits into your hand like a glove. Shutter release and all important controls are located ergonomically so you can operate the camera as you would on land. All of the camera's important functions can be operated underwater opening up the full capability of these sophisticated cameras to the underwater photographer. Changing film is done without removing the camera and removing the camera body to change lenses only takes a few seconds. The accurate positioning of the camera eliminates the possibility of mistakes. The new designed revolutionary QuickLock system locks the housing lid in a very easy, quick and secure way.

W x H x D:

Approx. 230 x 170 x 120 mm (w/o Port and accessories)

Weight:

Approx. 1,7 kg. (w/o Port and accessories)

Buoyancy:

Nearly neutral (depended on used Port and accessories)

Flash connector:

Nikonos V type, second TTL connector optional

Flash arm mounts:

Two 25mm T-plates, TLC- or Ultralight base optional

Max. Depth rating:

70 Meter (210 ft)

